

**Rushmore** Clean-Face Direct-Vent Fireplace Inserts WITH TRUFLAME TECHNOLOGY

# Rushmore







#### INSPIRING VERSATILITY


### Liners & Logs (ONE OF EACH REQUIRED)



Old World Stone



Rustic Brick



Black Glass



Traditional Charred Log Set



Driftwood Log Set

#### Surrounds & Fronts

(SURROUND REQUIRED; FRONT OPTIONAL)




Metal Surround Dimensions			
DVCT30CBN	DVCT35CBN		
36 x 24 x 1*	40 x 29 x 1*		
40 x 27 x 1	44 x 31 x 1		
42 x 29 x 1*	48 x 33 x 1*		
44 x 31 x 1	52 x 36 x 1		


<sup>\*</sup>Note: Also available in flush



Forged Iron Front



Forged Iron Front and Rectangle Inset (Front and Inset sold separately)



Forged Iron Front and Arch Inset (Front and Inset sold separately)

## TRUFLAME TECHNOLOGY Most Realistic Flames

Complementing the logs and giant ember bed, TruFlame Technology includes two burners for independent front/rear burner control of the ultra-realistic flames. With both burners in your control, you can call for a roaring fire, a low glow, or anywhere in between.

The multifunction remote operates as a conventional thermostat, a Smart Thermostat which modulates flame height as the room reaches the desired temperature, or as a manual control. The remote also operates the included accent light and blower.

#### STANDARD FEATURES

Your Rushmore Direct-Vent Insert includes an accent light and blower. Customize your insert further by choosing a liner and log set (both required), and finish it with a required surround and optional front.

- · Accent Light
- · Blower




Insert Dimensions			
DIMENSION	DVCT30CBN	DVCT35CBN	
Α	19"	24"	
В	30-11/16"	34-3/4"	
С	17-9/16"	18-9/16"	
G	21-11/16"	25-1/8"	
I	15-1/8"	17-1/8"	
J	5-7/8"	6-15/16"	
K	9-3/4"	9-1/4"	
L	16-7/16"	16-13/16"	
М	1-1/8"	1-13/16"	
N	15-1/4"	20-1/4"	
0	25-1/2"	29-1/2"	

FLUE 4" DIA

moori bimonsions			5103	
IMENSION	DVCT30CBN	DVCT35CBN		DVCT3
Α	19"	24"	Natural	30,000 /
В	30-11/16"	34-3/4"	LP	28,500 /
С	17-9/16"	18-9/16"	'Minimum with	front burner o
G	21-11/16"	25-1/8"		
I	15-1/8"	17-1/8"	Minim	um Firepla
J	5-7/8"	6-15/16"		DVCT3
K	9-3/4"	9-1/4"	Α	19-1
••	, 5, 1	'''	D	A 1 1

Btus (Max / Min)			
	DVCT30CBN	DVCT35CBN	
Natural	30,000 / 8,500*	39,000 / 10,000*	
LP	28,500 / 10,000*	35,000 / 11,000*	
***************************************			

Minimum Fireplace Opening Dimensions			
	DVCT30CBN	DVCT35CBN	
Α	19-1/2"	24-1/2"	
В	31-1/4"	35-1/4"	
С	18"	19"	
D	22"	25-3/4"	



Specifications			
Type of Gas	Natural or LP		
Iron Pipe Size (N.P.T.)	1/2-inch		
Ignition Systems	Multi Function Remote with IP		
Venting	3x4-inch Flex Vent		

Specifications			
Type of Gas	Natural or LP		
Iron Pipe Size (N.P.T.)	1/2-inch		
Ignition Systems	Multi Function Remote with IP		
Venting	3x4-inch Flex Vent		

111					
ш	$\boldsymbol{\sim}$	rr	$\boldsymbol{\smallfrown}$	nı	v
W	u		u	ш	-7

10-year limited warranty on combustion chamber, limited lifetime

All other parts carry a three-year limited warranty.

All remote controls carry a one-year limited warranty.

Member of the following industry associations:









This appliance is design-certified to the ANSI standard by:











Empire Comfort Systems Inc. 918 Freeburg Ave. Belleville, IL 62220-2623 info@empirecomfort.com WMH-01017 2/01/19

Empire is committed to continuous product improvement; specifications are subject to change without notice. Dimensions in this brochure are approximate; read and follow the framing dimensions in the owners manual supplied with your Empire product. Flame size, shape, and color will vary from photos.